

TKG® 500 (HMWPE)

#### Section 1. COMPANY AND PRODUCT IDENTIFICATION

Name: TRAID VILLARROYA HNOS. S.L.
Address: C/ Isabel de Santo Domingo 35

50014 Zaragoza

**SPAIN** 

E-mail: info@traidvillarroya.com
Website: www.traidvillarroya.com

Material Name: TKG® 500

HMWPE NATURAL AND COLOURS. Polyethylene (copolymer);

#### Section 2. COMPOSITION / INFORMATION ON COMPONENTS

Polyethylene, eventually Olefines - Copolymerisat, Stabiliser, Additives.

Additives in this product do not present a respiration hazard unless the product is ground to a powder of respirable size and the dust is inhaled. All dusts can potentially cause injury to the respiratory tract if respirable particles are generated and inhaled in sufficiently high concentrations. Good industrial hygiene practices, as with all dusts, should include precautions to prevent inhalation of respirable particles.

### **Section 3. HAZARDS IDENTIFICATION**

**Emergency Overview:** This material is NOT HAZARDOUS by OSHA Hazard Communication definition. Trade secret chemical identities will be revealed to treating physicians in an emergency or to purchasers after execution of a secrecy agreement.

HAZARDS: Molten material may cause thermal burns. At process temperatures irritating fumes may be produces.

 $\label{eq:Dustmay} \text{Dust may form explosive mixtures with air.}$ 

PHYSICAL STATE: Solid.

COLOUR: Translucent to white or opaque color.

ODOR: Faint, mild hydrocarbon odor.

**ODOR THRESHOLD:** No value available.

#### **Section 4. FIRST AID MEASURES**

**Eye contact:** Mechanical irritation is possible.

Skin contact: After contact with molten product cool quickly with cold water. Do not pull solidified product from skin.

Inhalation: Inhalation of process fumes and vapours may cause soreness in the nose and throat and coughing.

"Nuisance dust" such as polymer dust typically exhibits no significant health effect when they are

reasonably controlled. Exposure to high concentrations of dust may cause slight irritation by mechanical

action.

**Ingestion:** Ingestion not likely route of exposure.

### **Section 5. FIRE FIGHTING MEASURES**

Notice: To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither TRAID VILLARROYA HNOS. S.L. nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The most recent update can be found at <a href="https://www.traidvillarroya.com">www.traidvillarroya.com</a>.

INDS S. I.

Page 1 of 5



# TKG® 500 (HMWPE)

SMALL FIRE: Use dry chemical, CO2, water spray or regular foam.

LARGE FIRE: Use large quantities of water spray.

Special protective equipment for fire fighting:

PROTECTIVE EQUIPMENT/CLOTHING: Wear an approved positive pressure self-contains breathing apparatus and fire-

fighter turnout gear.

FIRE FIGHTING GUIDANCE: Polyolefin dust particles in the atmosphere are combustible and may be

explosive. Keep away from heat, sparks, flame and all other ignition sources.

Prevent dust accumulations and dust clouds.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic

acids, ketones, aldehydes and alcohols may be formed.

**Additional advice:** 

Flash Point: Not Applicable

Auto Ignition Temperature: Approx. 343°C (649°F)

**Section 6. ACCIDENTAL RELEASE MEASURES** 

Methods for cleaning up: Mechanical.

**Environmental precautions:** Before entry of swarf waste to sewage it should be mechanically cleaned of product remainders.

Section 7. <u>HANDLING AND STORAGE</u>

General advice: Keep away from heat, sparks, open flame, or any ignition source. Machine or process with

adequate ventilation. Machine shavings can make walking hazardous, potentially causing falls

and serious injury. After handling, always wash hand thoroughly with soap and water.

Technical measures: Keep dry. Store away from excessive heat and away from strong oxidizing agents.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Guidelines for materials: Ventilate area to prevent accumulation of dust or vapors.

Respiratory protection: A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2

requirements must be followed whenever workplace conditions warrant respirator use. Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. Use appropriate respiratory protection where

atmosphere exceeds recommended limits.

Eye protection: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due

to airborne particles which may result from handling this product. Safety glasses are required as

minimum requirements.

Skin protection: Use chemical resistant gloves appropriate to conditions of use. Wear heat protective gloves and

clothing if there is a potential for contact with heated material. Protective clothing such as long

sleeves or a lab coat should be worn.

Notice: To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither TRAID VILLARROYA HNOS. S.L. nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The most recent update can be found at <a href="https://www.traidvillarroya.com">www.traidvillarroya.com</a>.

Page 2 of 5



# TKG® 500 (HMWPE)

Work / hygiene practices:

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse. Material shavings on hard surface can be a serious slipping/falling hazard. Use care when walking shavings.

### Section 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Solid (semi finished or finished parts).

APPEARANCE: Translucent to white or opaque colored solid stock shape

ODOR: Odourless

ODOR THRESHOLD: No value available

pH: Not applicable

**BOILING POINT/BOILING RANGE:** Not applicable

**FREEZING POINT/MELTING POINT:** 136°C (276°F)

FLASH POINT: Not applicable

AUTO-IGNITION: around 343°C (649°F)

**FLAMMABILITY:** Not Classified. Polymer will burn but does not easily ignite.

LOWER FLAMMABLE LIMIT: Not applicable

**UPPER FLAMMABLE LIMIT:** Not applicable

**EXPLOSIVE PROPERTIES:** No data available

OXIDIZING PROPERTIES: No data available

VAPOR PRESSURE: Not applicable

**EVAPORATION RATE:** Not applicable

**RELATIVE DENSITY:** 0.94 - 0.97 (water = 1)

**RELATIVE VAPOR DENSITY:** Not applicable

SOLUBILITY (WATER): Insoluble

**Section 10. STABILITY AND REACTIVITY** 

Chemical stability: Stable under normal conditions of use, storage and transportation.

Notice: To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither TRAID VILLARROYA HNOS. S.L. nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The most recent update can be found at <a href="https://www.traidvillarroya.com">www.traidvillarroya.com</a>.

MINUS S. I.



# TKG® 500 (HMWPE)

Conditions to avoid: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

**Incompatibility with other materials:** Material may be softened by some hydrocarbons.

Hazardous decomposition products: Dependent on process conditions (>392°F, pressure, time, O2) hazardous decomposition

products may be generated.

Polymerization: Not likely.

**Section 11. TOXICOLOGICAL INFORMATION** 

COMPONENT INFORMATION: According to experience, the product is considered to be harmless to health if handled in the

correct manner.

INHALATION: Rats inhaling polyethylene dust developed mild inflammatory changes in the lungs. Prolonged

inhalation of thermal degradation products from polyethylene cause neurological effects in rats.

INGESTION: No adverse health effects were noted on the digestive system of test animals when fed up to 20%

polyethylene.

SKIN IRRITATION: No adverse effects are expected.

REPEATED DOSE TOXICITY: Subchronic, 50-90 day, feeding studies conducted on rats, dogs and swine showed no effects

from dietary levels of 1-20% powdered and shredded polyethylene.

CARCINOGENICITY: Not listed by IARC, NTP, or OSHA.

Section 12. ECOLOGICAL INFORMATION

• 1-HEXENE, POLYMER WITH ETHENE

**ECOTOXICITY:** Ecotoxicity is expected to be nominal based on the low water solubility of polymers.

**ENVIRONMENTAL FATE AND PATHWAY: Persistence and Degradability.** 

**Biodegradation:** This material is not expected to be readily biodegradeable.

**Bioaccumulation:** This material is not expected to bioaccumulate.

PROPRIETARY ADDITIVES

**ECOTOXICITY:** No data available.

ENVIRONMENTAL FATE AND PATHWAY: No data available.

Section 13. <u>DISPOSAL CONSIDERATIONS</u>

Use only licensed transporters and permitted facilities for waste disposal. Comply with federal, state, or local regulations for disposal. Recycle if possible.

**Section 14. TRANSPORTATION INFORMATION** 

Notice: To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither TRAID VILLARROYA HNOS. S.L. nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The most recent update can be found at <a href="https://www.traidvillarroya.com">www.traidvillarroya.com</a>.

hinds S. I.



TKG® 500 (HMWPE)

SPECIAL REQUIREMENTS: If you reformulate or further process this material, you should consider re-evaluation of the

regulatory status of the components listed in the composition section of this sheet, based on final

composition of your product.

**PROPER SHIPPING NAME:** POLYETHYLENE, OTHER THAN LIQUID.

**Section 15. <u>REGULATORY INFORMATION</u>** 

**REGULATORY STATUS** 

Labelling in accordance with GefStoffV / EC: Hazard warning labelling nto compulsory .

**Section 16. OTHER INFORMATION** 

Do not use in medical applications involving permanent implantation in the human body.

To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither TRAID VILLARROYA HNOS. S.L. nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

Notice: To the best of our knowledge, the information contained in this Material Safety Data Sheet is accurate. However, neither TRAID VILLARROYA HNOS. S.L. nor any of its representatives assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The most recent update can be found at <a href="https://www.traidvillarroya.com">www.traidvillarroya.com</a>.